

PRODUCT NAME SUPER STAIN REMOVER

4. FIRST AID MEASURES

Eye	Hold eyelids apart and flush continuously with water. Continue until advised to stop by the Poisons Information Centre, a doctor, or for at least 15 minutes. Keep patient calm.
Inhalation	If over exposure occurs leave exposure area immediately. If irritation persists, seek medical attention.
Skin	Remove contaminated clothing and gently flush affected areas with water. Continue to flush with water until skin no longer feels soapy. Seek medical attention. Launder clothing before reuse.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
Advice to Doctor	Treat symptomatically
First Aid Facilities	Eye wash facilities should be available. A hand wash basin is also recommended.

5. FIRE FIGHTING MEASURES

Flammability	Non flammable. May evolve toxic gases (hydrocarbons, carbon oxides) when heated to decomposition. May also evolve sulphur oxides and inorganic salts when heated to decomposition.
Fire and Explosion	Non flammable. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Non flammable. Prevent contamination of drains or waterways, absorb runoff with sand or similar.
Hazchem Code	2X

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt, absorb with sand or similar. Wear splash-proof goggles and PVC/rubber gloves. For large amounts, wear coveralls and rubber boots. Collect and place in sealable containers for disposal. Caution: Spill site may be slippery.
-----------------	---

7. STORAGE AND HANDLING

Storage	Store in cool, dry, well ventilated area, removed from oxidising agents, acids, active metals, direct sunlight, heat sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should be bunded and have appropriate ventilation systems.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards	No exposure standard(s) allocated.
Biological Limit Values	No biological limit allocated.
Engineering Controls	Do not inhale vapours. Use in well ventilated areas. In poorly ventilated areas, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.
PPE	Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear a faceshield, coveralls and boots. When using large quantities or where heavy contamination is likely, wear coveralls and a faceshield.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	WHITE COLOURED GRANULAR POWDER	Solubility (water)	SOLUBLE
Odour	SLIGHT DETERGENT ODOUR	Specific Gravity	NOT AVAILABLE

PRODUCT NAME SUPER STAIN REMOVER

pH	> 11.5	% Volatiles	0 %
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT AVAILABLE	Autoignition Temperature	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Material to Avoid	Incompatible with oxidising agents (eg. peroxides), acids (eg. sulphuric acid), active metals (eg. aluminium, potassium, magnesium), and heat and ignition sources.
Decomposition	May evolve toxic gases (hydrocarbons, carbon oxides) when heated to decomposition. May also evolve sulphur oxides and inorganic salts when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	This product has the potential to cause adverse health effects with eye contact or prolonged skin contact. Due to the low vapour pressure of this product an inhalation hazard is not anticipated with normal use. Use safe work practices to avoid direct eye or skin contact and vapour/ mist generation-inhalation.
Eye	May result in pain, redness, corneal burns and ulceration with possible permanent damage with prolonged contact.
Inhalation	Over exposure may result in irritation of the nose & throat with coughing, nausea and headache. Low vapour pressure reduces the inhalation hazard.
Skin	Prolonged and repeated contact may result in irritation, skin rash, dermatitis, blisters and burns.
Ingestion	Ingestion may result in ulceration to the mouth and throat with nausea and vomiting.
Toxicity Data	SODIUM METASILICATE ANHYDROUS (6834-92-0) LD50 (Ingestion): 770 mg/kg (mouse)

12. ECOLOGICAL INFORMATION


Environment	WATER: If released to waterways, alkaline products may change the pH of the waterway. Fish will die if the pH reaches 10-11 (goldfish 10.9, bluegill 10.5). SOIL: May leach to groundwater with toxic effects on aquatic life as above. ATMOSPHERE: Not expected to reside in the atmosphere. Drops or particles released to atmosphere should be removed by gravity and/or be rained out.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	DISODIUM TRIOXOSILICATE				
UN No.	3253	DG Class	8	Subsidiary Risk(s)	None Allocated
Pkg Group	III	Hazchem Code	2X	EPG	8A1

15. REGULATORY INFORMATION

Poison Schedule	Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

ABBREVIATIONS:

ADB - Air-Dry Basis.

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

TWA/ES - Time Weighted Average or Exposure Standard.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT and Ecowash Systems by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT and Ecowash Systems have taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT and Ecowash Systems accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

MSDS Date: 13 August 2007

End of Report